

High Speed Disc

| 10" BLADE SPACING | HS.8525 | HS.8530 | HS.8535 | HS.8540 |
|-------------------------------|---|------------------------|------------------------|------------------------|
| DIMENSIONS | | | | |
| Minimum Cut Width | 25' 5" (7.7m) | 30' 5" (9.3m) | 35' 5" (10.8m) | 40' 5" (12.3m) |
| Width, transport | 11' 10" (3.6m) | 11' 10" (3.6m) | 11' 10" (3.6m) | 11' 10" (3.6m) |
| Height, transport | 13' 5" (4.1m) | 13' 5" (4.1m) | 13' 5" (4.1m) | 13' 5" (4.1m) |
| Weight per ft. average | 1031 lbs/ft (1540 kg/m) | 947 lbs/ft (1410 kg/m) | 895 lbs/ft (1330 kg/m) | 854 lbs/ft (1270 kg/m) |
| Horsepower required | 335-425 hp | 335-425 hp | 390-480 hp | 450-550 hp |
| Working depth | 2.5" to 5" (64-127 mm) | | | |
| Working speed | 8 to 12 mph (13-19 kph) | | | |
| STRUCTURE | | | | |
| Frame, main frame | 8" x 4" x 0.5" (203 x 102 x 12.7 mm) | | | |
| Frame, cross member | 6" x 4" x 0.5" (152 x 102 x 12.7 mm) | | | |
| Bearings, 20" blades | Hub 30 bearing, double roller maintenance-free bearings, 4 mounting bolts for 20" blades | | | |
| Bearings, 22, 24 & 26" blades | Hub 40 bearing, double roller maintenance-free bearings, 6 mounting bolts for 22, 24 & 26" blades | | | |
| Blade angle, | Front blades at 17 degrees with a 20 degree pitch / rear blades at 15 degrees with a 20 degree pitch. | | | |
| BLADES | | | | |
| Blades, standard | 20" x 1/4" (508 x 6.5 mm) | | | |
| Blades, optional | 22" x 1/4" (508 x 6.5 mm) / 24" x 5/16" (609mm x 8 mm) / 26" x 5/16" (660mm x 8 mm) | | | |
| FEATURES | | | | |
| Tires, hitch frame | 600/50R22.SIMP SUPERFLOT TL | | | |
| Tires, wing frame | 600/50R22.SIMP SUPERFLOT TL | | | |
| Depth control | c/w depth stop segments at hitch cylinders and left hand wing rear cylinder | | | |
| ATTACHMENTS | | | | |
| Cage Rollers | 24" diameter w/10 1.5 diameter spiral round bars, three sections | | | |
| Spring Rollers | 24" diameter w/ four curved springs mounted on a spiral inner frame, three sections | | | |
| Rubber Rollers | 21.3" diameter with rubber pneumatic sleeve, three sections | | | |